

Talon®

# Double-Hung Windows & Talon RetroFit Windows



## Frame & Sash

① Select wood components are kiln dried, and treated with water/insect repellent and preservative. Interior wood surfaces are available in complimentary pine or mixed grain fir, or optional wood species including cherry, hickory, African mahogany, maple, oak, walnut, alder or vertical grain fir. Interior surfaces are available unfinished or factory primed. Optional factory-applied finishes are available in a variety of stains and basecoats.

② Wood components are fitted with aluminum extrusions on the exterior. 50 colors conforming to AAMA 2604 are available, as well as custom colors. Also available is a selection of seven exterior anodized options.

## Glazing

③ High-Performance™ Low-E4® glass with a low-conductance spacer. Tinted, clear IG, high-altitude glass and other special glazing options are available.

④ Glass is fixed in place from the interior with wood stops that can be removed for easy reglazing if necessary.

## Weather Strip

⑤ Compression bulb weather strip is applied on the bottom sash, head jamb, at the check rail and on side jambs for a maximum weather seal.

## Hardware

⑥ Talon sash lock/tilt mechanisms and keepers give a slim, more traditional design and allow opening and tilting of the window in one operation. Tilting the sash from the inside for cleaning is effortless.

Surface mount sash lifts are available and allow for easy operation.

Hardware is available in finishes of bronze, polished brass, gold, white, black, antique brass, pewter, oil-rubbed bronze, satin chrome and bright chrome.

# Features & Options

<p><b>6</b> <i>Sash Locks</i></p>	<p><b>7</b> <i>Rigid Jamb Liners</i></p>	<p><b>9</b> <i>Screens</i></p>
<p><i>Sash Lifts</i></p>	<p><b>8</b> <i>Replacement Sash Kit</i></p> <p><b>A</b> SASH <b>B</b> HARDWARE <b>C</b> SCREW PACK <b>D</b> SILL DAM <b>E</b> HEAD PARTING STOP <b>F</b> RIGHT AND LEFT COMPRESSION JAMB LINER AND BALANCE SYSTEMS</p>	<p><b>10</b> <i>Divided Lights</i></p> <p><b>MDL</b> = Modern Divided Lights <b>CDL</b> = Classic Divided Lights <b>Flat</b> = Between-glass grilles <b>Contoured</b> = Between-glass grilles <b>Removable</b> = Removable wood grilles</p>

## Jamb Liner & Balance System

**7** Talon double-hung jamb liners incorporate synthetic interior and exterior inserts or optional painted aluminum exterior or wood-veneered interior inserts.

Jamb liners encase balance assemblies that allow each sash to be tilted 90° inward from a bottom pivot and stay securely in place for washing.

## Window Anchorage

Optional folding vinyl nailing fins are pre-applied into a kerf on the frame exterior to facilitate installation. Optional metal installation clips are available.

## Talon RetroFit

Talon RetroFit double-hung fits into an existing window frame making installation a breeze. The appearance of the interior and exterior of the home are maintained because the existing frame, wall coverings and trim work stay completely intact. See page 50 for more details.

## Replacement Sash Kit

**8** Clad double-hung replacement sash kits are available. Kits are complete with window sashes, locking hardware and sash lifts, compression jamb liners and balance systems, sill dam, head parting stop and installation hardware. Each kit is built to your exact measurements. See page 52 for more details.

## Screens

Charcoal fiberglass screen mesh fits into an aluminum frame in all 50 Eagle Complimentary Colors™ and seven anodized finishes. Available in half or full screens. Aluminum screen mesh is available as an option.

TruScene® insect screens available in all complimentary colors and seven anodized finishes.

## Divided Lights

**Modern Divided Lights**®. Fixed interior and exterior grilles with internal spacers between two panes of glass. Available in 5/8", 7/8", 1 1/8" or 1 1/2" profiles.

**Classic Divided Lights**. Fixed exterior and interior grilles without an internal spacer. Available in 5/8", 7/8", 1 1/8" or 1 1/2" profiles.

**Between-glass grilles**. Available in 5/8" flat or 1" aluminum contoured profiles. Two-tone colors of colony white/pebble tan, colony white/sierra bronze or colony white/forest green are available on the 1" profile.

**Removable wood grilles**. Removable wood grilles are available in a 7/8" profile with optional surround and fixed exterior grilles.

# Eagle Window & Door

## Opening Tables

### Talon® Double-Hung Windows

Unit No.	Width (Inches)	Height (Inches)	Meets Egress Req.	Sq. Ft. Clear Opening	Clear Opening (Inches)		Sq. Ft. Vent	Sq. Ft. Daylight Opening	Glass Size (Inches)		Floor to Sill Height (Inches)
					Width	Height			Width	Height	
1830	20	36	No	1.28	15 11/16	11 3/4	1.28	2.34	13 15/16	14	49 7/16
1834	20	40	No	1.50	15 11/16	13 3/4	1.50	2.70	13 15/16	16	45 7/16
1840	20	48	No	1.93	15 11/16	17 3/4	1.93	3.41	13 15/16	20	37 7/16
1846	20	54	No	2.26	15 11/16	20 3/4	2.26	3.95	13 15/16	23	31 7/16
1849	20	57	No	2.42	15 11/16	22 1/4	2.42	4.22	13 15/16	24 1/2	28 7/16
1850	20	60	No	2.59	15 11/16	23 3/4	2.59	4.49	13 15/16	26	25 7/16
1851	20	61	No	2.64	15 11/16	24 1/4	2.64	4.58	13 15/16	26 1/2	24 7/16
1856	20	66	No	2.91	15 11/16	26 3/4	2.91	5.03	13 15/16	29	19 7/16
1860	20	72	No	3.24	15 11/16	29 3/4	3.24	5.57	13 15/16	32	13 7/16
1866	20	78	No	3.57	15 11/16	32 3/4	3.57	6.11	13 15/16	35	7 7/16
1870	20	84	No	3.89	15 11/16	35 3/4	3.89	6.65	13 15/16	38	1 7/16
1876	20	90	No	4.22	15 11/16	38 3/4	4.22	7.19	13 15/16	41	n/a
2030	24	36	No	1.61	19 11/16	11 3/4	1.61	3.06	17 15/16	14	49 7/16
2034	24	40	No	1.88	19 11/16	13 3/4	1.88	3.53	17 15/16	16	45 7/16
2040	24	48	No	2.43	19 11/16	17 3/4	2.43	4.47	17 15/16	20	37 7/16
2046	24	54	No	2.84	19 11/16	20 3/4	2.84	5.18	17 15/16	23	31 7/16
2049	24	57	No	3.04	19 11/16	22 1/4	3.04	5.53	17 15/16	24 1/2	28 7/16
2050	24	60	No	3.25	19 11/16	23 3/4	3.25	5.88	17 15/16	26	25 7/16
2051	24	61	No	3.32	19 11/16	24 1/4	3.32	6.00	17 15/16	26 1/2	24 7/16
2056	24	66	No	3.66	19 11/16	26 3/4	3.66	6.59	17 15/16	29	19 7/16
2060	24	72	No	4.07	19 11/16	29 3/4	4.07	7.29	17 15/16	32	13 7/16
2066	24	78	No	4.48	19 11/16	32 3/4	4.48	8.00	17 15/16	35	7 7/16
2070	24	84	No	4.89	19 11/16	35 3/4	4.89	8.70	17 15/16	38	1 7/16
2076	24	90	No	5.30	19 11/16	38 3/4	5.30	9.41	17 15/16	41	n/a
2430	28	36	No	1.93	23 11/16	11 3/4	1.93	3.78	21 15/16	14	49 7/16
2434	28	40	No	2.26	23 11/16	13 3/4	2.26	4.36	21 15/16	16	45 7/16
2440	28	48	No	2.92	23 11/16	17 3/4	2.92	5.53	21 15/16	20	37 7/16
2446	28	54	No	3.41	23 11/16	20 3/4	3.41	6.40	21 15/16	23	31 7/16
2449	28	57	No	3.66	23 11/16	22 1/4	3.66	6.83	21 15/16	24 1/2	28 7/16
2450	28	60	No	3.91	23 11/16	23 3/4	3.91	7.27	21 15/16	26	25 7/16
2451	28	61	No	3.99	23 11/16	24 1/4	3.99	7.42	21 15/16	26 1/2	24 7/16
2456	28	66	No	4.40	23 11/16	26 3/4	4.40	8.14	21 15/16	29	19 7/16
2460	28	72	No	4.89	23 11/16	29 3/4	4.89	9.01	21 15/16	32	13 7/16
2466	28	78	No	5.39	23 11/16	32 3/4	5.39	9.89	21 15/16	35	7 7/16
2470	28	84	Yes	5.88	23 11/16	35 3/4	5.88	10.76	21 15/16	38	1 7/16
2476	28	90	No	6.37	23 11/16	38 3/4	6.37	11.63	21 15/16	41	n/a
2630	30	36	No	2.10	25 11/16	11 3/4	2.10	4.14	23 15/16	14	49 7/16
2634	30	40	No	2.45	25 11/16	13 3/4	2.45	4.78	23 15/16	16	45 7/16
2640	30	48	No	3.17	25 11/16	17 3/4	3.17	6.05	23 15/16	20	37 7/16
2646	30	54	No	3.70	25 11/16	20 3/4	3.70	7.01	23 15/16	23	31 7/16
2649	30	57	No	3.97	25 11/16	22 1/4	3.97	7.49	23 15/16	24 1/2	28 7/16
2650	30	60	No	4.24	25 11/16	23 3/4	4.24	7.96	23 15/16	26	25 7/16
2651	30	61	No	4.33	25 11/16	24 1/4	4.33	8.12	23 15/16	26 1/2	24 7/16
2656	30	66	No	4.77	25 11/16	26 3/4	4.77	8.92	23 15/16	29	19 7/16
2660	30	72	No	5.31	25 11/16	29 3/4	5.31	9.88	23 15/16	32	13 7/16
2666	30	78	Yes	5.84	25 11/16	32 3/4	5.84	10.83	23 15/16	35	7 7/16
2670	30	84	Yes	6.38	25 11/16	35 3/4	6.38	11.79	23 15/16	38	1 7/16
2676	30	90	No	6.91	25 11/16	38 3/4	6.91	12.74	23 15/16	41	n/a
2830	32	36	No	2.26	27 11/16	11 3/4	2.26	4.50	25 15/16	14	49 7/16
2834	32	40	No	2.64	27 11/16	13 3/4	2.64	5.20	25 15/16	16	45 7/16
2840	32	48	No	3.41	27 11/16	17 3/4	3.41	6.58	25 15/16	20	37 7/16
2846	32	54	No	3.99	27 11/16	20 3/4	3.99	7.62	25 15/16	23	31 7/16
2849	32	57	No	4.28	27 11/16	22 1/4	4.28	8.14	25 15/16	24 1/2	28 7/16
2850	32	60	No	4.57	27 11/16	23 3/4	4.57	8.66	25 15/16	26	25 7/16

# Eagle Window & Door

## Opening Tables

### Talon® Double-Hung Windows

Unit No.	Width (Inches)	Height (Inches)	Meets Egress Req.	Sq. Ft. Clear Opening	Clear Opening (Inches)		Sq. Ft. Vent	Sq. Ft. Daylight Opening	Glass Size (Inches)		Floor to Sill Height (Inches)
					Width	Height			Width	Height	
2851	32	61	No	4.66	27 11/16	24 1/4	4.66	8.83	25 15/16	26 1/2	24 7/16
2856	32	66	No	5.14	27 11/16	26 3/4	5.14	9.70	25 15/16	29	19 7/16
2860	32	72	Yes	5.72	27 11/16	29 3/4	5.72	10.74	25 15/16	32	13 7/16
2866	32	78	Yes	6.30	27 11/16	32 3/4	6.30	11.78	25 15/16	35	7 7/16
2870	32	84	Yes	6.87	27 11/16	35 3/4	6.87	12.82	25 15/16	38	1 7/16
2876	32	90	No	7.45	27 11/16	38 3/4	7.45	13.85	25 15/16	41	n/a
3030	36	36	No	2.59	31 11/16	11 3/4	2.59	5.22	29 15/16	14	49 7/16
3034	36	40	No	3.03	31 11/16	13 3/4	3.03	6.03	29 15/16	16	45 7/16
3040	36	48	No	3.91	31 11/16	17 3/4	3.91	7.64	29 15/16	20	37 7/16
3046	36	54	No	4.57	31 11/16	20 3/4	4.57	8.84	29 15/16	23	31 7/16
3049	36	57	No	4.90	31 11/16	22 1/4	4.90	9.45	29 15/16	24 1/2	28 7/16
3050	36	60	No	5.23	31 11/16	23 3/4	5.23	10.05	29 15/16	26	25 7/16
3051	36	61	No	5.34	31 11/16	24 1/4	5.34	10.25	29 15/16	26 1/2	24 7/16
3056	36	66	Yes	5.89	31 11/16	26 3/4	5.89	11.25	29 15/16	29	19 7/16
3060	36	72	Yes	6.55	31 11/16	29 3/4	6.55	12.46	29 15/16	32	13 7/16
3066	36	78	Yes	7.21	31 11/16	32 3/4	7.21	13.67	29 15/16	35	7 7/16
3070	36	84	Yes	7.87	31 11/16	35 3/4	7.87	14.87	29 15/16	38	1 7/16
3076	36	90	No	8.53	31 11/16	38 3/4	8.53	16.08	29 15/16	41	n/a
3230	38	36	No	2.75	33 11/16	11 3/4	2.75	5.59	31 15/16	14	49 7/16
3234	38	40	No	3.22	33 11/16	13 3/4	3.22	6.45	31 15/16	16	45 7/16
3240	38	48	No	4.15	33 11/16	17 3/4	4.15	8.16	31 15/16	20	37 7/16
3246	38	54	No	4.85	33 11/16	20 3/4	4.85	9.45	31 15/16	23	31 7/16
3249	38	57	No	5.21	33 11/16	22 1/4	5.21	10.10	31 15/16	24 1/2	28 7/16
3250	38	60	No	5.56	33 11/16	23 3/4	5.56	10.74	31 15/16	26	25 7/16
3251	38	61	Yes	5.7	33 11/16	24 1/4	5.67	10.96	31 15/16	26 1/2	24 7/16
3256	38	66	Yes	6.26	33 11/16	26 3/4	6.26	12.03	31 15/16	29	19 7/16
3260	38	72	Yes	6.96	33 11/16	29 3/4	6.96	13.32	31 15/16	32	13 7/16
3266	38	78	Yes	7.66	33 11/16	32 3/4	7.66	14.61	31 15/16	35	7 7/16
3270	38	84	Yes	8.36	33 11/16	35 3/4	8.36	15.90	31 15/16	38	1 7/16
3430	40	36	No	2.91	35 11/16	11 3/4	2.91	5.95	33 15/16	14	49 7/16
3434	40	40	No	3.41	35 11/16	13 3/4	3.41	6.86	33 15/16	16	45 7/16
3440	40	48	No	4.40	35 11/16	17 3/4	4.40	8.69	33 15/16	20	37 7/16
3446	40	54	No	5.14	35 11/16	20 3/4	5.14	10.06	33 15/16	23	31 7/16
3449	40	57	No	5.51	35 11/16	22 1/4	5.51	10.75	33 15/16	24 1/2	28 7/16
3450	40	60	No	5.89	35 11/16	23 3/4	5.89	11.44	33 15/16	26	25 7/16
3451	40	61	Yes	6.01	35 11/16	24 1/4	6.01	11.67	33 15/16	26 1/2	24 7/16
3456	40	66	Yes	6.63	35 11/16	26 3/4	6.63	12.81	33 15/16	29	19 7/16
3460	40	72	Yes	7.37	35 11/16	29 3/4	7.37	14.18	33 15/16	32	13 7/16
3466	40	78	Yes	8.12	35 11/16	32 3/4	8.12	15.55	33 15/16	35	7 7/16
3470	40	84	Yes	8.86	35 11/16	35 3/4	8.86	16.93	33 15/16	38	1 7/16
3830	44	36	No	3.24	39 11/16	11 3/4	3.24	6.67	37 15/16	14	49 7/16
3834	44	40	No	3.79	39 11/16	13 3/4	3.79	7.70	37 15/16	16	45 7/16
3840	44	48	No	4.89	39 11/16	17 3/4	4.89	9.75	37 15/16	20	37 7/16
3846	44	54	No	5.72	39 11/16	20 3/4	5.72	11.29	37 15/16	23	31 7/16
3849	44	57	No	6.13	39 11/16	22 1/4	6.13	12.06	37 15/16	24 1/2	28 7/16
3850	44	60	No	6.55	39 11/16	23 3/4	6.55	12.83	37 15/16	26	25 7/16
3851	44	61	Yes	6.68	39 11/16	24 1/4	6.68	13.08	37 15/16	26 1/2	24 7/16
3856	44	66	Yes	7.37	39 11/16	26 3/4	7.37	14.36	37 15/16	29	19 7/16
3860	44	72	Yes	8.20	39 11/16	29 3/4	8.20	15.90	37 15/16	32	13 7/16
3866	44	78	Yes	9.03	39 11/16	32 3/4	9.03	17.44	37 15/16	35	7 7/16
4040	48	48	No	5.39	43 11/16	17 3/4	5.39	10.80	41 15/16	20	37 7/16
4046	48	54	No	6.30	43 11/16	20 3/4	6.30	12.51	41 15/16	23	31 7/16
4049	49	57	No	6.90	44 11/16	22 1/4	6.90	13.69	42 15/16	24 1/2	28 7/16
4050	48	60	No	7.21	43 11/16	23 3/4	7.21	14.21	41 15/16	26	25 7/16

# Eagle Window & Door

## Opening Tables

### Talon<sup>®</sup> Double-Hung Windows

Unit No.	Width (Inches)	Height (Inches)	Meets Egress Req.	Sq. Ft. Clear Opening	Clear Opening (Inches)		Sq. Ft. Vent	Sq. Ft. Daylight Opening	Glass Size (Inches)		Floor to Sill Height (Inches)
					Width	Height			Width	Height	
4051	48	61	Yes	7.36	43 11/16	24 1/4	7.36	14.50	41 15/16	26 1/2	24 7/16
4056	48	66	Yes	8.12	43 11/16	26 3/4	8.12	15.92	41 15/16	29	19 7/16
4060	48	72	Yes	9.03	43 11/16	29 3/4	9.03	17.63	41 15/16	32	13 7/16

**Notes:**

Floor to sill height is based on structural header heights of 6' 10-1/2" and is calculated from the top of the subfloor to the top of the inside sill stop.

Egress Requirements: 5.7 sq. ft. minimum clear opening area, 20" minimum clear opening width, 24" minimum clear opening height, 44" maximum floor to sill height.

Code restrictions may vary depending on your local building codes.

If glass is positioned within 18" of the floor, safety/tempered glass may be required by code.

Eagle Window & Door reserves the right to change specifications without notice.

Rev. 12/07

# Eagle Window & Door

*Talon® Double-Hung*  
 3050 Tested Size at DP 40  
 Series 07 Clad Talon Double Hung

Glass Type	Divided Light Options	U-VAL	SHGC	VLT	CR	Energy Star Zone
High-Performance™ Low-E4™ 2.2mm / 11.5mm / 2.2mm	No Between-glass Grilles or MDL	0.32	0.30	0.51	52	2
	7/8" CDL	0.32	0.27	0.46	52	2
	1-1/8" & 1-1/2" CDL	0.32	0.24	0.40	52	2
	5/8" Between-glass Grilles	0.33	0.27	0.46	52	2
	1" Between-glass Grilles	0.33	0.27	0.46	52	2
	5/8" MDL	0.33	0.27	0.46	52	2
	7/8" MDL	0.33	0.27	0.46	52	2
	1-1/2" MDL	0.36	0.24	0.40	52	8
	1-1/8" MDL	0.34	0.24	0.40	52	2
High-Performance™ Low-E4™ High Altitude 2.2mm / 11.5mm / 2.2mm	No Between-glass Grilles or MDL	0.35	0.30	0.51	49	2
	7/8" CDL	0.35	0.27	0.46	49	2
	1-1/8" & 1-1/2" CDL	0.35	0.24	0.40	49	2
	5/8" Between-glass Grilles	0.37	0.27	0.46	49	8
	1" Between-glass Grilles	0.37	0.27	0.46	49	8
	5/8" MDL	0.37	0.27	0.46	49	8
	7/8" MDL	0.37	0.27	0.46	49	8
	1-1/2" MDL	0.39	0.24	0.40	49	8
	1-1/8" MDL	0.38	0.24	0.40	49	8
High-Performance™ Low-E4™ Gray Tint 3.1mm / 9.8mm / 3.0mm	No Between-glass Grilles or MDL	0.33	0.27	0.35	51	2
	7/8" CDL	0.33	0.24	0.31	51	2
	1-1/8" & 1-1/2" CDL	0.33	0.22	0.27	51	2
	5/8" Between-glass Grilles	0.34	0.24	0.31	51	2
	1" Between-glass Grilles	0.34	0.24	0.31	51	2
	5/8" MDL	0.34	0.24	0.31	51	2
	7/8" MDL	0.34	0.24	0.31	51	2
	1-1/2" MDL	0.35	0.22	0.27	51	2
	1-1/8" MDL	0.34	0.22	0.27	51	2
High-Performance™ Low-E4™ Gray Tint High Altitude 3.1mm / 9.8mm / 3.0mm	No Between-glass Grilles or MDL	0.37	0.27	0.35	48	8
	7/8" CDL	0.37	0.25	0.31	48	8
	1-1/8" & 1-1/2" CDL	0.37	0.22	0.27	48	8
	5/8" Between-glass Grilles	0.38	0.25	0.31	48	8
	1" Between-glass Grilles	0.38	0.25	0.31	48	8
	5/8" MDL	0.38	0.25	0.31	48	8
	7/8" MDL	0.38	0.25	0.31	48	8
	1-1/2" MDL	0.39	0.22	0.27	48	8
	1-1/8" MDL	0.38	0.22	0.27	48	8
High-Performance™ Low-E4™ Bronze Tint 3.1mm / 9.8mm / 3.0mm	No Between-glass Grilles or MDL	0.33	0.28	0.38	51	2
	7/8" CDL	0.33	0.25	0.34	51	2
	1-1/8" & 1-1/2" CDL	0.33	0.23	0.29	51	2
	5/8" Between-glass Grilles	0.34	0.25	0.34	51	2
	1" Between-glass Grilles	0.34	0.25	0.34	51	2
	5/8" MDL	0.34	0.25	0.34	51	2
	7/8" MDL	0.34	0.25	0.34	51	2
	1-1/2" MDL	0.35	0.23	0.29	51	2
	1-1/8" MDL	0.34	0.23	0.29	51	2

# Eagle Window & Door

*Talon® Double-Hung*  
 3050 Tested Size at DP 40  
 Series 07 Clad Talon Double Hung

Glass Type	Divided Light Options	U-VAL	SHGC	VLT	CR	Energy Star Zone
High-Performance™ Low-E4™ Bronze Tint High Altitude 3.1mm / 9.8mm / 3.0mm	No Between-glass Grilles or MDL	0.37	0.28	0.38	48	8
	7/8" CDL	0.37	0.26	0.34	48	8
	1-1/8" & 1-1/2" CDL	0.37	0.23	0.29	48	8
	5/8" Between-glass Grilles	0.38	0.26	0.34	48	8
	1" Between-glass Grilles	0.38	0.26	0.34	48	8
	5/8" MDL	0.38	0.26	0.34	48	8
	7/8" MDL	0.38	0.26	0.34	48	8
	1-1/2" MDL	0.39	0.23	0.29	48	8
Low-E 240 3.0mm / 9.8mm / 3.1mm	No Between-glass Grilles or MDL	0.33	0.19	0.28	51	2
	7/8" CDL	0.33	0.17	0.25	51	2
	1-1/8" & 1-1/2" CDL	0.33	0.15	0.25	51	2
	5/8" Between-glass Grilles	0.34	0.17	0.25	51	2
	1" Between-glass Grilles	0.34	0.17	0.25	51	2
	5/8" MDL	0.34	0.17	0.25	51	2
	7/8" MDL	0.34	0.17	0.25	51	2
	1-1/2" MDL	0.36	0.15	0.22	51	8
Low-E 240 High Altitude 3.0mm / 9.8mm / 3.1mm	No Between-glass Grilles or MDL	0.37	0.19	0.28	48	8
	7/8" CDL	0.37	0.17	0.25	48	8
	1-1/8" & 1-1/2" CDL	0.37	0.16	0.25	48	8
	5/8" Between-glass Grilles	0.38	0.17	0.25	48	8
	1" Between-glass Grilles	0.38	0.17	0.25	48	8
	5/8" MDL	0.38	0.17	0.25	48	8
	7/8" MDL	0.38	0.17	0.25	48	8
	1-1/2" MDL	0.39	0.16	0.22	48	8
Low-E 366 2.2mm / 11.5mm / 2.2mm	No Between-glass Grilles or MDL	0.31	0.20	0.46	52	2
	7/8" CDL	0.31	0.18	0.41	52	2
	1-1/8" & 1-1/2" CDL	0.31	0.16	0.36	52	2
	5/8" Between-glass Grilles	0.33	0.18	0.41	52	2
	1" Between-glass Grilles	0.33	0.18	0.41	52	2
	5/8" MDL	0.33	0.18	0.41	52	2
	7/8" MDL	0.33	0.18	0.41	52	2
	1-1/2" MDL	0.35	0.16	0.36	52	2
Low-E 366 High Altitude 2.2mm / 11.5mm / 2.2mm	No Between-glass Grilles or MDL	0.35	0.20	0.46	50	2
	7/8" CDL	0.35	0.18	0.41	50	2
	1-1/8" & 1-1/2" CDL	0.35	0.16	0.36	50	2
	5/8" Between-glass Grilles	0.37	0.18	0.41	49	8
	1" Between-glass Grilles	0.37	0.18	0.41	49	8
	5/8" MDL	0.37	0.18	0.41	49	8
	7/8" MDL	0.37	0.18	0.41	49	8
	1-1/2" MDL	0.38	0.16	0.36	49	8
1-1/8" MDL	0.37	0.16	0.36	49	8	

U-Factor - Rate of Heat Loss = 1/R  
 SHGC - Solar Heat Gain Coefficient  
 VLT- Visible Light Transmittance  
 CR - Condensation Resistance